



## PRODUCT DATA SHEET

Multi Purpose Food Grade Grease, 14 Wt Oz  
Part Number: SL35600



Product Description	An aluminum complex premium grade USDA H1 grease for use in food production and processing industries. This NLGI Grade 2 multi-purpose lubricant is white in color and has a smooth buttery texture.
Applications	Anywhere lubrication is needed where it may come in contact with food, bottling machinery, breweries, canneries, carton/packaging equipment, dairies, food processing & handling equipment, meat processing plants, seamers at high speeds & pressure,
Unit Package Description	14 Ounce Cartridge
Brand	Sta-Lube
Generic Description 1	Multi-purpose Food Grade Grease
Net Fill	14 Wt Oz
UPC Code	072213356007
Unit Dimensions	9.25H x 2.2W x 2.2D in
Units Per Case	10
Case Dimensions	9.6H x 4.6W x 11D in
Cases Per Pallet	150
Case Weight	10 lbs
I 2 of 5 Code	30072213356008
Appearance	White Semi-Solid to Solid Grease
Base Type	Aluminum Complex
Flash point (F)	430°F
Flash point (C)	221°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.89 at 60°F
NLGI Grade	2
Timken OK Load [Lbs.]	40 Lbs
Plastic Safe	Not Determined
Evaporation Rate	<1 (butyl acetate=1)

Last revised: 7/15/2015  
Page 1 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



## PRODUCT DATA SHEET



Working Temp (F)	-30 to 300°F
Working Temp (C)	-34.4 to 149°C
4 Ball EP	500 Kg Weld
4 Ball Wear	0.6 mm typical
Drop Point	500°F
Oil Separation	Not Determined
Oxidation Stability	5
Pour Point (F)	0°F
Pour Point (C)	-17.78°C
ISO Viscosity Grade	68
Water Washout	5
Worked Penetration	265 to 295
Propellant	None
NSF Category Code	H1
NSF Number	132939
DOT Proper Shipping Name	Not Regulated
VOC % (Federal)	0.3
VOC g/L (Federal)	2.67
VOC Lbs./Gal. (Federal)	0.022
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser or brake cleaner product.

Last revised: 7/15/2015  
Page 2 of 2



Customer Care: 800-556-5074  
Technical Assistance: 800-521-3168  
[www.crcindustries.com](http://www.crcindustries.com)

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.